

	ADAM Audio T7V 7"	Mackie MR824 8"	Tannoy GOLD 7 6.5"	Yamaha HS8 8"
Powered	Yes	Yes	Yes	Yes
Power Configuration	Bi-amped	Bi-amped	Bi-amped	Bi-amped
LF Driver Size	7" woofer	8" woofer	6.5" woofer	8" woofer
LF Driver Type	Polypropylene	Polypropylene		Cone
HF Driver Size	1.9" U-ART tweeter	1" tweeter	1" tweeter	1"
HF Driver Type		Silk dome	Titanium	Dome
LF Driver Power Amp	50W	55W, 110W Peak		75W
HF Driver Power Amp	20W	30W, 60W Peak		45W
Total Power		85W Class A/B	300W Class-AB	120W
Frequency Range				38Hz-30kHz
Frequency Response	39Hz-25kHz	38Hz-20kHz (-3dB)	65 Hz - 20 kHz ±3 dB	
Crossover Frequency	2600Hz	24 dB/octave @ 1.9kHz	1.5 kHz	2kHz
Maximum Peak SPL	≥110dB SPL @ 1m	113 dB SPL @ 1m per pair	110 dB SPL @ 1m	
Input Types	1 x XLR, 1 x RCA	1 x 1/4", 1 x XLR, 1 x RCA	1 x 1/4", 1 x XLR, 1 x 1/8" (aux)	1 x XLR, 1 x 1/4" TRS
Output Types			1 x 1/8" (monitor link)	
Features		Low frequency 3-way switch, High frequency 3-way filter		
Enclosure Type	Rear ported	Rear ported	Front Ported	Ported
Enclosure Material		MDF wood cabinet	MDF with Black Vinyl wrap	
Height	13.7"	15.7"	14"	15.4"
Width	8.3"	10.1"	8.7"	9.8"
Depth	11.5"	12.6"	11.3"	13.1"
Weight	15.7 lbs.	23 lbs.	20.7 lbs.	22.5 lbs.
Price/Pair	\$500.00	\$540.00	\$630.00	\$740.00
Detailed Specs	DATA SHEET	DATA SHEET	DATA SHEET	DATA SHEET

Source: <https://www.sweetwater.com/>

For additional specs click on the data sheet links