

	KRK V6 S4 6.5"	Mackie HR624mk2 6"	Dynaudio LYD 7 7"	ADAM Audio A7X 7"
Powered	Yes	Yes	Yes	Yes
Power Configuration	Bi-amped	Bi-amped	Bi-amped	Bi-amped
LF Driver Size	6.5" woofer	6.7" woofer	7" woofer	7" woofer
LF Driver Type		Cone		Woofer Material: Carbon, Rohacell, Glass Fiber
HF Driver Size	1" tweeter	1"	1.1" tweeter	2" X-ART tweeter
HF Driver Type		Dome	Soft dome	
LF Driver Power Amp	125W	100W	50W	100W
HF Driver Power Amp	30W	40W	50W	50W
Total Power	155W	140W	100W Class D	
Frequency Range	40Hz-24kHz	49Hz-20kHz (± 1.5 dB)		
Frequency Response	49Hz-19kHz		45Hz-21kHz	42Hz-50kHz
Crossover Frequency		3kHz, 24 dB/octave	4.3kHz	2500Hz
Maximum Peak SPL	115 dB SPL	106 dB	109 dB SPL @ 1m	≥ 114 dB SPL @ 1m
Input Types	1 x XLR-1/4" combo	1 x XLR, 1 x TRS, 1 x RCA	1 x XLR, 1 x RCA	1 x XLR, 1 x RCA
Features	High/Low shelf EQ settings, dB level attenuation		3-way bass switch, 3-way sound balance, 2-way position switch, sensitivity settings	
Enclosure Type	Ported	Sealed	Rear Ported	Ported
Height	13.89"	13.1"	12.6"	13.5"
Width	9"	8.6"	7.3"	8"
Depth	11.34"	12.6"	11.6"	11"
Weight	20.7 lbs.	23.4 lbs.	17.6 lbs.	20.3 lbs.
Price/Pair	\$1200.00	\$1200.00	\$1300.00	\$1500.00
Detailed Specs	DATA SHEET	DATA SHEET	DATA SHEET	DATA SHEET

Source: <https://www.sweetwater.com/>

For additional specs click on the data sheet links